

49 RANGER PRO

2020



ROTAX® ENGINE

	600R E-TEC	900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	599.4 cc	899.0 cc
Bore	72,3 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane		95
Fuel tank		37 liters
Oil tank capacity (2-stroke)	3,4 liters	-

POWERTRAIN

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	Radien-X
Skis	Blade DS
Seating	2-up light
Handlebar	U-type steel with hooks, mountain strap
Riser block height	140 mm
Starter	Electric (900 ACE) Electric, Manual (600R E-TEC)
Reverse	RER (600R E-TEC) Mechanical (900 ACE)

COLOUR



DIMENSIONS

Vehicle overall length	3540 mm
Vehicle overall width	1105 mm (600R E-TEC) 1180 mm (900 ACE)
Vehicle overall height	1490 mm
Ski stance	921 +/- 21 mm (600R E-TEC) 996 +/- 21 mm (900 ACE)
Track nominal width	406 mm
Track nominal length	4141 mm
Track profile height	59 mm Powder Max FlexEdge

SUSPENSION

Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide
Center shock	HPG 36
Rear shock	HPG 36

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2-in. wide digital display
Mirrors	-
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Yes, in glove box